



NEW PRODUCTS

FG-1B-1009

FlameGuard™ Male Adapter Featuring CPVC Lined Male Brass Thread



Spears® revolutionary design features a special molded-in-place brass male thread that is fully lined with CPVC for superior corrosion resistance. Available in sizes 3/4" through 2"


- Designed for Plastic to Metal Transitions
- CPVC lined for Increased Corrosion Resistance
- Wrench Flats Provide Easy Installation

Compatible with all Brands of Approved CPVC Fire Sprinkler Products

FlameGuard™ Male Adapters should be installed using Spears® Blue 75™ Thread Sealant that has been tested for compatibility with FlameGuard™ CPVC Fire Sprinkler Products.

Male Adapter- MIPT X Socket

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
4236-007	3/4	40	160	076	20.87
4236-010	1	10	60	076	24.60
4236-012	1-1/4	10	80	076	27.11
4236-015	1-1/2	10	80	076	29.85
4236-020	2	5	20	076	40.95



Part Number	L	M1	N	Approx. Wt. (Lbs.)
4236-007	2-17/32	1-13/32	13/16	.26
4236-010	2-29/32	1-23/32	29/32	.43
4236-012	3-1/8	2-3/32	31/32	.66
4236-015	3-9/32	2-11/32	31/32	.80
4236-020	3-7/16	2-7/8	31/32	1.00

NOT FOR USE WITH COMPRESSED AIR OR GAS

Prices subject to change without notice. Possession of this price schedule shall not be construed as an offer to sell the products listed. Product drawing(s) & photo(s) are representative and may not fully reflect product configuration.

Progressive Products From Spears® Innovation & Technology



SPEARS® MANUFACTURING COMPANY • CORPORATE OFFICE
15853 Olden St., Sylmar, CA 91342 • PO Box 9203, Sylmar, CA 91392
(818) 364-1611 • www.spearsmfg.com

